



V33 TEAK OIL



Impregnates in-depth. Long term performance

➔ **NOURISHES – PROTECTS – EMBELLISHES**
➔ **TEAK AND EXOTIC WOOD**

- High resistance to UV and water
- Anti-stain and anti-grease protection
- Waterproofing – Dry in 3 hours

Natural oil for protecting and maintaining all outdoor furniture made of teak or exotic wood.

- ➔ Nourishes and protects against water, sunlight, stains and grease.
- ➔ Microporous: lets the wood breathe.
- ➔ Preserves contact with the wood and its natural appearance.
- ➔ Once dry, does not stain clothes.

Application

The wood must be bare, clean and dry.

- **Rough timber or oiled wood:** Sand lightly and remove the dust.
- **Surface coated wood:** Sand and remove dust.

- **1st application:** Stir well before use. Pour the Teak Oil into the cover of the pack. Impregnate the wood liberally, by applying the first coat with a flat brush. Let it dry for 6 hours then apply a second coat. After about 10 minutes, wipe off the excess using a lint-free cotton cloth.
- **Maintenance:** At the start and end of the season, apply a coat of oil using a flat brush. Let it penetrate for 10 min then wipe off the excess with a cloth.

V33 Advice

- ➔ To make sure that your wood is sufficiently oiled, let a few drops of water run on it. If these pearl-off at the wood surface, the wood is waterproofed. Otherwise, apply another coat of oil.
- ➔ In case of local wear or clouding, apply a little oil using a cloth or with an Oil spray.
- ➔ The appearance may vary depending on the varieties of wood. Perform a test on a hidden portion of your piece of furniture.

Waterproofing agent – Reinforced Anti UV

Covering power in 1 coat: 1L = + or – 12 m²

Drying time: To touch: 3 h – Between coats: 6 h - Complete: 24 h

Equipment: flat brush, piece of cloth

Cleaning: White spirit or V33 Cleaning Solvent

Safety recommendations and Precautions for use



SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE

WARNING - EUH208: Contains methylethylketoxime. May produce an allergic reaction.

H226: Flammable liquid and vapour. EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority)

CAUTION: to avoid fire hazard, dispose of used cloths in an air tight container

NOVENTA A.E
Πεθύμνου 1
106 82 Αθήνα
Τél : 210 – 8218502

G.S. Hadjiyiannis Logistics Ltd
PO Box 55004
3820 Limassol - Cyprus
Τél : +357-25-877430

www.v33.com