



PEINTURE SOL EXTREME TRAFFIC TRAFFIC EXTRÊME FLOOR PAINT

Paint based on urethane alkyd resin for improved protection of floors with high traffic.

Purpose

Suitable for all types of surfaces: cement, concrete, bricks, floors...

Suitable inside and outside for: garages, basements, stairs, driveway, storerooms, laundry rooms.

Characteristics

- Strong resistance to frequent car traffic, abrasion and hot tyres
- Resistant to stains and grease: it protects the floor from oils, chemical products...
- Strongly resistant to scuffmarks and shocks, tool marks, abrasion...
- Direct application on prepared cement or concrete floors
- Water and UV protection
- 6h between coats to finish painting in one day.

Preparation

Essential before painting the floor.

The surface has to be clean, dry, porous, not greasy or powdery.

ROUGH SURFACES:

- **New concrete:** allow to dry for 3 months before painting.
- **Rough cement / concrete:** degrease with V33 Cement-Concrete Active Cleaner.

Check for porosity by sprinkling water on the floor. If the drops stay on the surface, then the floor is not porous and the paint will not adhere. Apply hydrochloric acid mixed with water (1L of acid for 4L of water) to make the concrete porous. Rinse. Allow to dry for 48 hours.

- **Parquet floor, wooden floor, wood:** sand and remove dust.
- **Metal :** remove rust and degrease.

PAINTED SURFACES:

- Wash, sand with coarse abrasive paper and remove as much old paint as possible. Remove dust.

PRECAUTIONS ON FLOOR FILLER:

- New filler : check with the manufacturer for compatibility.
- Old filler : test on a small surface for adhesion.

Application

Before each use, stir with a long wide stick to mix the paint thoroughly. Ideal application conditions: between 10° and 25°.

- Apply the first coat (diluted with 5% white spirit) on rough cement, concrete or wood floors. Allow the 1st coat to dry for 4 to 6 h before applying the 2nd coat. After 6 h, sand before applying the 2nd coat for improved adhesion. On very porous floors or floors with high traffic, a 3rd coat may be necessary.
- Reusable after: 24 hours for foot traffic and 72 hours for car traffic.



Colours : 9 colours

Aspect : Satin

Packaging: 0.5L – 2.5L-3L- 5L

Drying time:

Touch dry: 8h

Fully dry: 24h

Coverage in 1 coat:

± 14 sqm / L depending on the porosity of the surface

Tool cleaning: white spirit

Material : brush, medium-pile roller



PEINTURE SOL FLOOR PAINT

TRAFIC EXTRÊME EXTREME TRAFFIC



COLOUR CHART



V33 S.A – B.P.1 – F-39210 Domblans – Customer services: 03 84 35 00 00

This is an informative notice. The information provided is based on our knowledge and our present experience with conditions of use in compliance with applicable standards and building regulations. Considering the many different factors that can influence the use of V33 products, the information does not relieve users from experimenting by themselves. This document is not legally binding. It cancels and replaces the previous ones.