

# BEESWAX

with pure turpentine



150 ml

*Liberon Beeswax is ideal for nourishing absorbent woods such as pine and oak, especially unsealed or for use on items that have been dipped for stripping. A natural protector of wood, it guards against dryness and is particularly suitable for small surfaces and furniture.*

## INSTRUCTIONS FOR USE

2h-4h

Drying time



Tools: Steelwool  
or cloth



Tools cleaning:  
Turpentine or  
White Spirit



150ml = 1-2m<sup>2</sup>

**Preparation:** Remove old waxes and dirt with Liberon Wax and Polish Remover if necessary. Ensure the surface is clean, dry and free from dust.

**Application:** Apply a coat of Liberon Beeswax sparingly with a soft, lint-free cotton cloth or Liberon Ultra Fine Steel Wool (0000). Allow to dry for 2 hours, or until touch dry, then buff with a clean cotton cloth, Liberon Wax Polishing Brush or Liberon Drill Brush. Repeat the operation on new or very dry wood as it may require two or more coats. For a higher sheen, build-up with thin coats of Beeswax, buffing between coats.

**Important:** Always test product on a spare surface or inconspicuous area for colour, compatibility and end results.

**Cleaning and maintenance:** Wipe over with a cloth or duster and re-wax as required when the surface looks dull and tired. Do not wash with water.

### Precautions

- Not suitable for high water areas such as kitchens and bathrooms. We recommend the use of Liberon oils or varnishes in these areas.

## LIBERON SECRET

*Our Beeswax is compatible with other waxes available in the Liberon range. For water marks, apply wax to the mark and spread evenly with a rag.*

## COLOUR CHART

