





500 ml





www.saberindustrial.com

sales@saberindustrial.com

+961-9-546 540

Features

- Quick acting and easy to apply
- Fast evaporation
- 2-way use
- · Eco friendly









Instructions

Spilled foam should be removed immediately using DYNA-FIX® Gun & Foam Cleaner. Cured foam must be removed mechanically.
Apply with the can upside-down.
Screw the can directly onto the gun and pull the trigger several times at intervals of 10 seconds for internal foam applicator cleaning.
Use red adapter to spray cleaner and clean the gun externally.









Designed & Manufactured According to AFAQ ISO 9001:2015 Certified Quality Management System

Technical Data

Property	Unit	Value	
Color	22 - V	Clear	9

Priming

This product features adhesion to a variety of non-porous substrates; however, for specific substrates, priming may be necessary to improve adhesion. Please consult our Technical Service Department. Surface should be dampened.

Shelf Life

10 years from date of production, when stored at or below 25°C in the original unopened container

Packaging

• 500 mL can

The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-FIX® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-FIX® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.